

$$C_d = 0.98$$

$$Q = C_d \cdot A_1 A_2 \cdot \sqrt{2gh}$$
$$\sqrt{A_1^2 - A_2^2}$$

$$Q = \frac{0.98 \times 0.031 \times 7.85 \times 10^{-3} \times \sqrt{2 \times 9.81 \times 22.08}}{\sqrt{0.031^2 - (7.85 \times 10^{-3})^2}}$$

$$Q = 8.05 \times 10^{-3} \times 20.81$$

$$Q = 0.167 \text{ m}^3/\text{sec.}$$

$$A_0 = A \left(\frac{1.5}{4} \right)^2 = 0.0177 \text{ m}^2, A_1 = A \left(\frac{0.30}{4} \right)^2 = 0.0177 \text{ m}^2$$

$$y = \frac{S_0 \sin \theta}{2g} = 0.5 \text{ m} \text{ Hg}, S_{\text{gail}} = 0.9, C_d = 0.64$$

$$h = y \left[\frac{S_{\text{gail}}}{S_{\text{gail}}} - 1 \right] = 0.5 \left[\frac{13.6}{0.9} - 1 \right]$$

$$h = 7.05 \text{ m}$$

$$Q = C_d A_1 A_0 \sqrt{2gh}$$
$$\sqrt{A_1^2 - A_0^2}$$

$$Q = \frac{0.64 \times 0.0177 \times 0.0177 \times \sqrt{2 \times 9.81 \times 7.05}}{\sqrt{0.0177^2 - 0.0177^2}}$$

$$= \frac{9.4193 \times 10^{-3}}{0.0685} = 0.1376 \text{ m}^3/\text{sec.}$$

$$y = \frac{170 \text{ mm} \text{ Hg}}{S_{\text{gail}}} = \frac{0.17 \text{ m} \text{ Hg}}{1.026}, S_{\text{gail}} = 1.026$$

$$A_h = y \left[\frac{S_{\text{gail}}}{S_{\text{gail}}} - 1 \right] = 0.17 \left[\frac{13.6}{1.026} - 1 \right]$$

$$A_h = 2.08 \text{ m}$$

$$V = \sqrt{2gA_h} = \sqrt{2 \times 9.81 \times 2.08}$$

$$V = 6.388 \text{ m/s}$$

5. $Q = 0.05 \text{ dm}^3/\text{min} = 8.33 \times 10^{-5} \text{ m}^3/\text{sec}$
 Speed of rotation = 1700 Rev/min = 28.3 rev/sec
 Nominal displacement = $10 \text{ cm}^3/\text{rev} = 10^{-5} \text{ m}^3/\text{rev}$
 Torque Input = 15 Nm
 Pressure change = 15 bar = $15 \times 10^5 \text{ N/m}^2$
 Ideal Flowrate = Nominal displacement \times Speed of rotation
 $= 10^{-5} \times 28.3 = 2.83 \times 10^{-4} \text{ m}^3/\text{sec}$

a. Volumetric Efficiency = $\frac{\text{Actual Flowrate}}{\text{Ideal Flowrate}} \times 100$
 $= \frac{8.33 \times 10^{-5}}{2.83 \times 10^{-4}} \times 100 = 29.45\%$

b. Fluid Power, $P_f = Q \times \Delta P$
 $= 8.33 \times 10^{-5} \times 15 \times 10^5 = 124.95 \text{ Watts}$

c. Shaft Power = $T \times \omega$
 $\omega = 2 \times \pi \times \text{Speed of rotation} = 2 \times \pi \times 28.3$
 $= 177.81 \text{ rad/sec}$

\therefore Shaft power = $15 \times 177.81 = 2667.2 \text{ Watts}$

d. Overall Efficiency = $\frac{\text{Fluid Power}}{\text{Shaft Power}} \times 100$
 $= \frac{124.95}{2667.2} \times 100 = 4.68\%$

ATOSWE VICTORIA ALDIYE.

18/ENG008/003.

BIO MEDICAL ENGINEERING.

ENG 214.



$$P_1 = \frac{P_2}{\rho} = 2.5 \text{ m/s}$$

$$H_2 = 0.35 (v_1 - v_2)^2$$

$$\frac{P_1}{\rho} + \frac{v_1^2}{2g} + z_1 = \frac{P_2}{\rho} + \frac{v_2^2}{2g} + z_2 + H_L$$

$$\frac{P_2}{\rho} = \frac{P_1}{\rho} + \frac{v_1^2 - v_2^2}{2g} + (z_1 - z_2) - 0.35 (v_1 - v_2)^2$$

$$\frac{P_2}{\rho} = 2.5 + \frac{5^2 - 2^2}{2(9.81)} + 2 - 0.35 (5 - 2)^2$$

$$\frac{P_2}{\rho} = 2.5 + 1.07 + 2 - 0.161$$

$$\frac{P_2}{\rho} = 5.409 \text{ m of liquid}$$

$$2. d = 200 \text{ mm} = 0.2 \text{ m}, d_2 = 100 \text{ mm} = 0.1 \text{ m}$$

$$P_1 = 17.658 \text{ N/cm}^2 = 176580 \text{ N/m}^2, P_2 = -0.3 \text{ cm Hg}$$

$$A_1 = \pi (0.1)^2 = 0.0314 \text{ m}^2, A_2 = \pi (0.05)^2 = 0.00785 \text{ m}^2$$

$$A_2 = \frac{A_1 (v_1)^2}{v_2^2} = 7.85 \times 10^{-3} \text{ m}^2$$

$$h = \frac{P_1 - P_2}{\rho} = \frac{176580}{(1000 \times 9.81)} = (-0.3 \times 13.6)$$

$$h = 18 + 4.08 = 22.08 \text{ m}$$