

Oreoluwa Ayodele Arinted

18/ENG031052

CIVIL ENGINEERING

FLUID MECHANICS

- 1) Given sp of gravity of $D_1 = 150\text{mm} = 0.15\text{m}$, $D_2 = 72\text{mm} = 0.072\text{m}$
 $Z_2 - Z_1 = 150\text{mm} = 0.15\text{m}$, $Q = 40\text{lit/sec} = 0.04\text{m}^3/\text{s}$
 $C_d = 0.96$

Pressure difference $\langle P_1 - P_2 \rangle$

$$A_1 = \frac{\pi D_1^2}{4} = \frac{\pi \times 0.15^2}{4} = 0.01767\text{m}^2$$

$$A_2 = \frac{\pi D_2^2}{4} = \frac{\pi \times 0.072^2}{4} = 0.00412\text{m}^2$$

$$Q = \frac{C_d \times A_1 A_2 \times \sqrt{2gh}}{\sqrt{A_1^2 - A_2^2}}$$

$$0.04 = \frac{0.96 \times 0.01767 \times 0.00412 \times \sqrt{2 \times 9.81 \times h}}{\sqrt{0.01767^2 - 0.00412^2}}$$

$$0.04 = 0.96 \times 0.004565 \times 4.429 \sqrt{h}$$

$$h = \left(\frac{0.04}{0.96 \times 0.004565 \times 4.429} \right) = 4.247\text{m}$$

$$h = \left(\frac{P_1}{\rho} + Z_1 \right) - \left(\frac{P_2}{\rho} + Z_2 \right)$$

$$h = \left(\frac{P_1}{\rho} + \frac{P_2}{\rho} \right) + (Z_1 - Z_2)$$

$$4.247 = \left(\frac{P_1 - P_2}{\rho g} \right) = -0.15$$

$$4.247 + 0.15 = \frac{P_1 - P_2}{\rho g}$$

$$(4.247 + 0.15) \rho g = P_1 - P_2$$

$$P_1 - P_2 = (0.8 \times 1000 \times 9.81)(4.247 + 0.15)$$

$$P_1 - P_2 = 34.59 \text{ kN/m}^2$$

2) Diameter of Inlet $D_1 = 300\text{mm} = 0.3\text{m}$
 Area of Inlet $A_1 = \frac{\pi \times D_1^2}{4} = \frac{\pi \times 0.3^2}{4} = 0.07\text{m}^2$

Diameter of throat $D_2 = 150\text{mm} = 0.15\text{m}$
 Area of water inlet $A_2 = \frac{\pi D_2^2}{4} = \frac{\pi \times 0.15^2}{4} = 0.01767\text{m}^2$

Specific gravity of heavy liquid (mercury) in U tube manometer
 $S_{hc} = 13.6$

Specific gravity of liquid (oil) flowing through pipe $SP = 0.9$
 Reading of differential manometer $y = 750\text{mm} = 0.75\text{m}$

The differential "h" is given by

$$h = \left(\frac{P_1}{w} + Z_1 \right) - \left(\frac{P_2}{w} + Z_2 \right)$$

$$= y \left(\frac{S_{hc}}{SP} - 1 \right) = 0.75 \left(\frac{13.6}{0.9} - 1 \right) = 3.53\text{m of Oil}$$

* Discharge of 0.1 Q
 Using the relation

$$Q = C_d \times A_1 \times A_2 \times \sqrt{2gh} \times \frac{1}{\sqrt{A_1^2 - A_2^2}}$$

$$Q = 0.98 \times 0.07 \times 0.01767 \times \sqrt{2 \times 9.81 \times 3.53} \times \frac{1}{\sqrt{0.07^2 - 0.01767^2}}$$

$$Q = 0.1487\text{m}^3/\text{s}$$

2) Pressure Difference between entrance and throat section
 $P_1 - P_2$ we know that:

$$h = \left(\frac{P_1}{w} + Z_1 \right) - \left(\frac{P_2}{w} + Z_2 \right) = 3.53$$

$$h = \left(\frac{P_1}{w} - \frac{P_2}{w} \right) - (Z_1 - Z_2) = 3.53$$

$$z_2 - z_1 = 300 \text{ mm} = 0.3 \text{ m}$$

$$\left(\frac{p_1 - p_2}{w} \right) - 0.3 = 3.53$$

$$\frac{p_1 - p_2}{w} = 3.53 + 0.3$$

$$\frac{p_1 - p_2}{w} = 3.83$$

$$p_1 - p_2 = 3.83w$$

$$p_1 - p_2 = 3.82 \times 9.81 \times 0.9$$

$$= 33.8 \text{ kN/m}^2$$