

Question 3:

OKPODU JESSICA ONAJITE

18/ENG07/010

Petroleum Engineering

ENG 214: Fluid Mechanics (Power)

Question 1:

Length of Tube = 2.0 m

$$V_1 = 5 \text{ m/s}$$

$$\rho_g = 2.5 \text{ m}$$

$$V_2 = 2 \text{ m/s}$$

$$h_L = \frac{0.35(V_1 - V_2)^2}{2g}$$

$$= \frac{0.35(5-2)^2}{2 \times 9.81} = \frac{0.35 \times 9}{2 \times 9.81}$$

$$\text{Pressure head} = \frac{P_1}{\rho_g} + \frac{V_1^2}{2g} + Z_1 = \frac{P_2}{\rho_g} + \frac{V_2^2}{2g} + Z_2 + h_L$$

$$\frac{2.5}{2 \times 9.81} + 2.0 = \frac{P_2}{\rho_g} + \frac{2^2}{2 \times 9.81} + 0 + 0.16$$

$$2.51 + 1.27 + 2.0 = \frac{P_2}{\rho_g} + 0.203 + 1.6$$

$$\frac{P_2}{\rho_g} = ((2.5) + (1.27) + (2.0)) - (0.203 + 0.16)$$

$$= \underline{\underline{5.407 \text{ m}}}$$

Question 2

Diameter at Inlet:

$$d_1 = 20 \text{ cm}$$

$$a_1 = \frac{\pi}{4} \times d_1^2$$

$$= \frac{\pi \times 20^2}{4} = 314.16 \text{ cm}^2$$

Diameter at Outlet: $d_2 = 10 \text{ cm}$

$$a_2 = \frac{\pi \times 10^2}{4} = 78.74 \text{ cm}^2$$

$$P_1 = 17.658 \text{ N/cm}^2$$

$$= 17.658 \times 10^4 \text{ N/m}^2$$

density of water = 1000 kg/m^3

$$\frac{P_1}{\rho g} = \frac{17.658 \times 10^4}{9.81 \times 1000} = 1.8 \text{ m}$$

$$\frac{P_2}{\rho g} = -30 \text{ cm of mercury}$$

$$= -0.30 \times 13.6$$

$$= -4.08 \text{ of water}$$

$$h_L = \frac{P_1}{\rho g} - \frac{P_2}{\rho g} = 1.8 - (-4.08)$$

$$= 1.8 + 4.08$$

= 2208 cm of water

$$\text{discharge } Q = Q = C_d = \frac{a_1 a_2}{\sqrt{a_1^2 + a_2^2}} \times \sqrt{2gh}$$

$$= 0.98 \times 314.16 \times 78.74 \times \sqrt{2 \times 9.81 \times 2208}$$

$$\sqrt{(3.14 \cdot 16)^2 - (78.74)^2}$$

$$= \frac{50328837.21}{304} \times 16555 \text{ cm}^2/\text{s}$$

$$= 165555 \text{ litres/seconds}$$

9%

Question 3:

Diameter of orifice = 15cm

$$\text{Area of the orifice} = a_0 = \frac{\pi}{4} (15)^2 \\ = 176.7 \text{ cm}^2$$

Diameter of pipe = $d_1 = 30\text{cm}$

$$\text{Area of the pipe} = a_1 = \frac{\pi \times 30^2}{4} = 706.85 \text{ cm}^2$$

Specific Gravity = 0.9

Differential manometer length = 50cm of mercury

$$\therefore \text{Differential Head} = 2h \left(\frac{S_1}{S_0} - 1 \right) = 50 \left(\frac{13.6}{0.9} - 1 \right)$$

$$= 50 \times 14.11 \\ = 705.5 \text{ cm of oil}$$

$$\therefore \text{The rate of flow } Q = C_d \times a_0 a_1 \times \sqrt{2gh} \\ \sqrt{a_1^2 - a_0^2}$$

$$= \frac{0.64 \times 176.7 \times 706.85}{\sqrt{(706.85)^2 - (176.7)^2}} \times \sqrt{2 \times 9.81 \times 705.5}$$

$$= \frac{94046317.78}{684.4}$$

$$= 137414.25 \text{ cm}^3/\text{s}$$

$$\underline{\underline{v = 137.414 \text{ litres/seconds}}}$$

Question 4:

Differential of mercury, $z = 170 \text{ mm}$
 $= 0.17 \text{ m}$

Specific gravity of Mercury = 13.6

Specific gravity of sea-water = 1.026

$$h = x \left(\frac{S_1}{S_2} - 1 \right)$$

$$= 0.17 \left(\frac{13.6}{1.026} - 1 \right)$$

$$= 2.0834 \text{ m}$$

$$\therefore V = \sqrt{2gh} = \sqrt{2 \times 9.81 \times 2.0834}$$
$$= 6.393 \text{ m/s}$$

$$= \frac{6.393 \times 60 \times 60}{1000}$$

$$= \underline{\underline{23.07 \text{ km/hr}}}$$

Question 5:

Actual flow rate = $5 \text{ dm}^3/\text{min}$

$$5 \text{ dm} = 1 \text{ m}$$

$$5 \text{ dm}^3 = x$$

$$\text{Volumetric flow rate} = x = \frac{5}{1000}$$

$$= 0.005 \text{ m}^3/\text{min}$$

$$\text{Actual flow rate} = \frac{0.005}{60 \text{ seconds}}$$

$$\text{①} = 8.33 \times 10^{-4} \text{ m}^3/\text{seconds}$$

Speed, $N = 1700 \text{ rev/min}$
 $= \frac{1700}{60} = 28.33 \text{ rev/seconds}$
 $= 28.33 \text{ rps}$

Pressure, $\delta P = 15 \text{ bar}$
 $\alpha = 15 \times 10^5 \text{ N/m}^2$

$\delta P = 15 \times 10^5 \text{ N/m}^2$

Normal displacement = $10 \text{ cm}^3/\text{rev}$
 $10 \text{ cm}^3 = 1 \text{ m}^3$

$\alpha = 10 / 1000000$
 $\alpha = 1 \times 10^{-5} \text{ m}^3/\text{rev}$

Ideal flow rate = normal \times speed displacement
 $= 28.33 \times 1 \times 10^{-5}$
 $= 2.833 \times 10^{-4} \text{ m}^3/\text{sec}$

(A) Volumetric Efficiency = $\frac{\text{Actual flow rate} \times 100\%}{\text{Ideal flow rate}}$
 $= \frac{8.33 \times 10^{-4} \times 100\%}{2.833 \times 10^{-4}}$
 $= 29.4\%$

(B) Fluid Power $P_f = Q \times \delta P$
 $= 8.33 \times 10^{-4} \times 15 \times 10^5$
 $= 1249.5 \text{ Nm/seconds}$

(C) Shaft Power = $T = 15 \text{ Nm}$
 $W = \frac{2\pi N}{60} = 2 \times \frac{22}{7} \times 28.33$
 $= 178.02 \text{ rad/seconds}$

\therefore Shaft Power = 15×178.02
 $= 2670.3 \text{ watts}$

(D) Overall Efficiency = $\frac{\text{Fluid Power} \times 100\%}{\text{Shaft Power}}$
 $= \frac{1249.5 \times 100\%}{2670.3} = 46.79\%$

c) Shaft Power = $T = 15 \text{ Nm}$

$$W = \frac{2\pi N}{60}$$

$$W = \frac{2 \times 20}{7} \times 2\pi \cdot 33$$

$$= 178.09 \text{ rad/seconds}$$

\therefore Shaft Power = 15×178.09

$$= 2670.3 \text{ Watts}$$

d) Overall Efficiency = $\frac{\text{Fluid Power}}{\text{Shaft Power}} \times 100\%$

Shaft Power

$$= \frac{1249.5}{2670.3} \times 100\%$$

$$= 46.79\%$$