

Balogun Oluwajun Akinola
18/ENIG03/020
Civil Engineering

$$1) v = 5 \text{ m s}^{-1}, v_2 = 2 \text{ m s}^{-1}$$

$$P_{T1} = 2.5 \text{ m}, P_{T2} = ?$$

$$P_{T1} = P_{T2} = \frac{0.35(v_1 - v_2)^2}{2g} = \frac{0.35 \times 3^2}{2 \times 9.81} = 0.161$$

$$\therefore P_{T1} - P_{T2} = 0.161$$

$$2.5 - P_{T2} = 0.161$$

$$P_{T2} = 2.5 - 0.161$$

$$P_{T2} = 2.67 \text{ m}$$

$$2) 200$$

$$= 0.20 \text{ m}$$

$$A = \pi d^2; P_T = \frac{\pi (0.20)^2}{4} = 0.0314 \text{ m}^2$$

$$P_1 = 17.658 \text{ N/cm}^2 = \frac{17.658}{10^{-6}} = 17658000$$

Specific gravity of mercury = 13.6

$$\frac{P_1}{10} = \frac{P_1}{\rho g} = \frac{17.658 \times 10^{-6}}{1000 \times 9.81} = 1.8 \times 10^{-7}$$

$$\text{Vacuum pressure} = \frac{P_2}{10} = 300 \text{ mm Hg}$$

$$d_2 = 100 \text{ mm} = 0.1$$

$$-0.30 \times 13.6 \quad A_2 = \frac{\pi d^2}{4} = \frac{\pi (0.10)^2}{4} = 7.85 \times 10^{-3}$$

$$P_2 = -4.08$$

$$h = 1.8 \times 10^{-7} + 4.08$$

$$= 4.080000002 \text{ m}$$

$$h = \frac{P_1}{\omega} - \frac{P_2}{\omega}$$

$$Q_{\text{actual}} = \frac{C_d A_1 A_2 \sqrt{2gh}}{\sqrt{A_1^2 - A_2^2}}$$

$$= \frac{0.98 \times 0.0314 \times 7.85 \times 10^{-3} \sqrt{2 \times 9.81 \times 4.080000002}}{\sqrt{(0.0314)^2 - (7.85 \times 10^{-3})^2}}$$

$$= 0.07108691665$$

$$3) d_1 = 150 \text{ mm} = 0.15 \text{ m}$$

$$\text{Pipe diameter } d_2 = 300 \text{ mm} = 0.30 \text{ m}$$

$$A_2 = \frac{\pi d_2^2}{4} = \frac{3.142 \times 0.15^2}{4} = 0.0177 \text{ m}^2$$

$$A_1 = \frac{\pi d_1^2}{4} = \frac{3.142 \times 0.30^2}{4} = 0.0707 \text{ m}^2$$

$$y = 500 \text{ mm Hg} = 0.50 \text{ m Hg}$$

$$C_d = 0.64$$

$$h = \frac{\text{S.G of Hg} - \text{S.G of oil} \times y}{\text{S.G of oil}}$$

$$= \frac{13.6 - 0.9 \times 0.5}{0.9}$$

$$= 7.06 \text{ m}$$

$$\text{Rate of flow, } Q_{\text{actual}} = \frac{C_d A_2 A_1 \sqrt{2gh}}{\sqrt{A_1^2 - A_2^2}}$$

$$Q_{\text{actual}} = \frac{0.64 \times 0.0707 \times 0.0177 \sqrt{2 \times 9.81 \times 7.06}}{\sqrt{(0.0707)^2 - (0.0177)^2}}$$
$$= 0.1377$$

$$4) v = \sqrt{2gh}$$

$$H = y \left(\frac{\text{S.G of mercury} - \text{S.G of water}}{\text{S.G of water}} \right)$$

$$H = 0.17 \left(\frac{13.6 - 1.026}{1.026} \right)$$

$$= 0.17 \times 12.26$$

$$= 2.0842 \text{ m}$$

$$v = \sqrt{2 \times 9.81 \times 2.0842}$$

$$= 6.39 \text{ ms}^{-1}$$

$$\therefore \text{Speed of submarine} = 6.39 \text{ ms}^{-1}$$

5) Actual flow rate $Q = 5 \text{ dm}^3/\text{min} = 8.33 \times 10^{-5} \text{ m}^3/\text{sec}$

$p = 15 \text{ bar} = 15 \times 10^5 \text{ N/m}^2$

$\gamma = 1700 \text{ rev/min} = 28.33 \text{ rev/sec}$

$T = 15 \text{ N/m}$ normal displacement $= 100 \text{ cm}^3/\text{rev}$
 $= 1 \times 10^{-5} \text{ m}^3/\text{rev}$