

ITEM	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
1	P and M point wiring in concealed in walls, furniture's & for above false ceiling, or on ceiling, on beams shall be fixed with metal saddles & metal spacers etc., with conduits taken in slab with 20 mm dia PVC Rigid conduits 1.5 mm thick ISI mark with 2 nos. of 1.5 sq. mm. & 1 nos. of 1.0 sq. mm. FRLS type wire with modular switch with company made flush metal box/surface PVC box etc. comp. with nec. main lines for switch board from LDB of mains of 2 nos. of 2.5 sq.mm wire and 1 no.of 1.50 sqmm pvc Insulated copper conductor FRLS type wire laying in with 20 mm/25 mm dia PVC rigid conduits 1.5 mm thick ISI mark .3 point cieling rose need to be provided for each points.These will be used with point wiring of light, fan, ex. fan, callbell points, etc { Max. 3 Switchboards in one circuit - One Sp MCB }				
a	One 5A switch controlling one light/fan point 3	no	35		
b	One switch controlling Two light points	no	3		
c	One switch controlling Three light points	no	3		
d	5A socket outlet with 5A switch (on common board)	no	3		

EKEOGUU IZUCHUKWU
17/ENG04/019
ENG 384 SHORT TEST

